

19" Metal Case CCTV LCD Monitor



- Supports up to 1280x1024 resolution
- 3D Comb-filter & 3D De-interlace
- HDMI Output
- BNC Connectors of Video Input/Output
- 4:3 Display ratio for security camera
- Anti-glare Technology
- OSD control & adjustments
- Acrylic Protection Front
- Industrial Heavy Duty Case



ADM-19M



1. Power: DC12V
2. PC Audio
3. Audio Input
4. Video In/Out
5. Video In/Out
6. S-Video
7. VGA
8. HDMI



The rack mount bracket can tilt up or down to optimize the viewing angle.

*noted: rack mount bracket (optional)



The adjustable bracket on the rear of unit allows table top use if desired.



The metal case has a standard VESA mount on the rear panel.

Model	ADM-19M
Resolution (max.)	1280x1024(SXGA); 1024x768(XGA); 800x600(SVGA); 640x480(VGA)
Displayable colors	16.7M
Brightness	350 cd/m ²
Contrast Ratio	800:1
Response Time	5ms
Aspect Ratio	4:3
Input/Output	VGA; HDMI; BNC; S-Video PC Mini Audio; CVBS Audio
Power Supply	DC12V
Power Consumption	45W (max.); Saving mode: 3W
Dimension	433(W) x 355(L) x 53(D) mm
Weight	8.1kg
Operation Temp.	0°C to +40°C (32°F to +104°F)
On Screen Display	
Color adjustment	Contrast, Brightness, Gamma Correct, Color Adjust
Picture adjustment	H-Position, V-Position, Sharpness, Phase, Clock
Function adjustment	Auto Adjust, Auto Position, Auto Phase, Auto Clock, Auto Color
OSD Menu	Language, OSD Timer, Translucent, OSD H-Position, OSD V-Position
OSD control buttons	Menu/Auto/+/-