

Infrared Weatherproof Bullet Camera



480
TVL



OSD



High
Light
Compensation



Backlight
Compensation



60M



IP 66



Day/Night



Digital
Noise
Reduction



Dead
Pixel
Compensation



Auto
Tracking
White Balance



Wide
Dynamic
Range



Anti-
Flicker



AIR-497



Avoid Spot Light

Various angle LED combination to avoid spot light.

Double Glass Design

The IR Light can not leak into the video sensor inside the camera.
The design effectively reduces the internal reflections.

Suitable for Outdoor Environment

With its built-in sun shield/rain shield, it's perfect for outdoor surveillance.



Power AC110V

Convenient for installation


Video BNC connector

BNC camera connection for easy plug-n-play setup



Easy Camera Setup

The 3-dimensional mini joystick on video/camera cable gives the user quick access to the OSD menu.



OSD Control

Model	AIR-497
Image Sensor	1/3" Sharp Color CCD
Resolution	480 TV Lines
Effective Pixels	NTSC: 510x492 / PAL: 500x582 (H)x(V)
Min. Illumination	0.1 Lux @ F1.8
Lens	6mm Fixed Lens
S/N Ratio	More than 50dB(AGC OFF)
Electronic Shutter	1/60(1/50)~1/100,000sec
Video Output	1.0Vp-p/75 ohm Composite
Sync. System	Internal
OSD	Built-in OSD Menu
White Balance	ATW/AWC(PUSH LOCK)/Manual
Shutter/AGC	Auto/Manual/FLK
Backlight	BLC/HLC
IR LED	102pcs
IR Distance	60M (200')
Weatherproof	IP 66
Power Source	AC100V~240V
Dimensions	142 (W)x 115 (H)x 310 (L) mm
Weight	800g
Operating Temp.	-10°C to +50°C (-14°F to +122°F)